



## 4nm 360° amber strobe (black), horizontal mount, with 0,7m cable

200-023G2S-B

4nm 360° amber strobe (blk), hor mnt, 0.7m  
Horizontal mounted with 0,75M cable.

Specifications	
Number	200-023G2S-B
Light Color	Yellow
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	IEC 60945
Visibility	3nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013360
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343013363
Connection	0.7m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	300
<b>Stock status</b>	Made to order
<b>Current consumption (mA @ 24VDC)</b>	151
<b>Vessel size</b>	All Sizes
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.52 Kg
<b>Weight (Oz)</b>	18.34 Oz