


For the latest content and full diesel product portfolio, visit MercuryMarine.com/Diesel

Speciications	150 mHP 230 mHP 270 mHP						
Compression ratio	16.5:1						
Fuel pre-filtration requirement	Not required but feasible						
Fuel lift pump	On engine						
High pressure fuel pump	Bosch CP 4.2 w/integrated gear lift pump						
Valves per cylinder	4						
Pistons	Oil jet cooled						
Fuel injectors	Bosch CRS 2.20 (Solenoid)						
Air Inlet (Port rear)	Filtered and silenced						
Turbocharger	Honeywell VGT						
Engine and turbocharger cooling	Closed cooled						
Coolers; CAC, Oil, Fuel and Engine	Tube and Shell						
Seawater pump/inlet mm (in)	38 mm (1.5in)						
Peak torque at RPM N-m (ft-lb)	493 Nm @ 2000 rpm 503 Nm @ 2200 rpm 594 Nm @ 2200 rpm						
Oil sump volume L (qt)	8.5L						
Dipstick range L (qt)	1.0L						
Oil maintenance interval hr*	200						
Flywheel size mm (in)	290 (11.42)						
Flywheel housing	SAE 8						
Electrical system	12V 110A						
Engine stop	ECU Controlled						
Engine Control Unit (ECU)	Bosch EDC17						
Throttle and shift	Mercury DTS or Mechanical Cable						
Helm and gauge compatibility	Mercury SmartCraft						
Mercury Joystick Piloting - Inboard & Sterndrive	Compatible						
Engine and ECU covers	Texture coated Aluminum. Protects engine plus provides step capable platform						
Inboard: ZF 63A	1.21, 1.56, 2.03, 2.52, 2.68						
Inboard: ZF 63	1.25, 1.75, 2.78						
Inboard: ZF 68IV	1.29, 1.56, 1.99						
Inboard: ZF 45C	1.00						
Sensors	Crank & cam position, intake manifold pressure/temp, compressor outlet temp, exhaust gas temp, fuel temp, rail pressure, water in fuel (WIF), oil pressure/ temp, coolant temp, seawater pressure/temp, atmospheric pressure						

Model	Driveline Options	Output Power		Fuel use at	Rated	Idle	Max Rated	Emissions Ratings (no after treatment)		
		mHP	kW	Rated Speed L/hr (gal/hr)	Use	Speed (RPM)	Engine Speed (RPM)	EPA	EU	ІМО
150	Bobtail Inboard	150	110	31.5 (8.3)	LDC	650	3000	Tier 3	RCD 2	Tier 2
230	Bobtail Inboard	230	169	49 (12.9)	REC/ LDC		4200	Tier 3		
270	Bobtail Inboard	270	199	55 (14.3)						


ENGINE DIMENSIONS - INBOARD



ENGINE DIMENSIONS - STERNDRIVE








TORQUE & POWER (full load at crankshaft)

BOAT LOAD FUEL CONSUMPTION





✓ 289mm → 236mm →

847mm



 \rightarrow

572mm

-<mark>420mm</mark>-

© 2018 Mercury Marine. A division of Brunswick Corporation. All rights reserved. Unauthorized reproduction prohibited

GO BOLDLY.