



2nm 360° Red+2nm 360° White, black anodized, with 0,7m cable

200-014+012G2-B

2nm 360° Red+2nm 360° White, black anodized
Horizontally mounted with 0.75m cable

Specifications	
Number	200-014+012G2-B
Light Color	Red,White
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.7"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012103
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343012106
Connection	0.7m cable

Specifications	
Current consumption (mA @ 12VDC)	150
Stock status	Made to order
Current consumption (mA @ 24VDC)	85
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1 Kg
Weight (Oz)	35.27 Oz