



2nm 135° stern light, single, vertical mount, black anodised, with 6m cable

301-006-B 6M

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Vertically mounted with 6m cable

Specifications	
Number	301-006-B 6M
Light Color	White
Dimensions metric	86,2 x 28 x 57,75
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a 1.1"="" 2.27"<="" href="https://www.lopolight.com.under-Service-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lopolight.com.under-www.lop</th></tr><tr><th>Intensity</th><th>>5.4cd</th></tr><tr><th>Dimensions imperial</th><th>3.3" th="" x="">
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438012912
IP rating	IP68
Power draw (W)	1,3
UPC Code	879343012915
Connection	6m cable



Specifications	
Current consumption (mA @ 12VDC)	110
Stock status	Made to order
Current consumption (mA @ 24VDC)	50
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm2 AWG22
Weight (Kg)	0.41 Kg
Weight (Oz)	14.46 Oz