



## 2nm Starboard, black w/FB base

301-008-FB-B

2nm Starboard, black w/FB base  
Horizontal mounted with 2,5m cable

Specifications	
Number	301-008-FB-B
Light Color	Green
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Support</a>
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,Installation guide,precabled with 2.5 meter shielded marine grade cable
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438043688
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343043810
Connection	2.5m cable
Current consumption (mA @ 12VDC)	110

Specifications	
<b>Current consumption (mA @ 24VDC)</b>	60
<b>Vessel size</b>	Under 12M,12-20M,20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0 Kg
<b>Weight (Oz)</b>	0.00 Oz