



## 6nm Masthead, black anodized

300-137-B

6nm Masthead, black anodized  
Vertically mounted with. 0,75m cable

Specifications	
Number	300-137-B
Light Color	White
Dimensions metric	107 x 92,5 x 74
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>94cd
Dimensions imperial	4.2" x 3.6" x 2.9"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	6nm
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438008519
IP rating	IP68
Power draw (W)	13
UPC Code	879343008512
Connection	0.7m cable
Current consumption (mA @ 12VDC)	0

Specifications	
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	580
<b>Vessel size</b>	Over 50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	1.07 Kg
<b>Weight (Oz)</b>	37.74 Oz