



SPL-12W



SPL-12B



SPL-12C

new product:

# Precision Wireless Controlled Spotlight

Marinco's innovative, new Precision Wireless Controlled Light addresses the most common issues found in marine-grade spotlights. In doing so it has become the most versatile, durable, consistent and easy-to-use spotlight on the market. Its unique, totally enclosed housing design protects all critical components from moisture, salt, shock and vibration for long-lasting operation. Whether mounted upright or suspended upside down, you get 370° sweep rotation and 120° tilt (75° up, 45° down) in a durable IP56 weatherproof housing. Inside, a brilliant 100 Watt H3 Halogen lamp with an optimized parabolic reflector pierces the ultra clear lens to provide a consistent light pattern.

Bright 100 Watt halogen bulb

Uniform 132 sq. ft coverage with 370° rotation and 120° tilt

Durable, weatherproof housing

Universal 12V or 24V operation

Wireless control



**MARINCO**

new product:

# Precision Wireless Controlled Spotlight

**3 YEAR WARRANTY**

## Specifications

Bulb:	100 Watt, H3 Halogen
Power (Input voltage):	12V or 24V
Current draw (idle/in use):	0.03 amps / 7.0 amps
Peak Beam Intensity:	210,000 Cp
Peak Beam Distance:	917 ft (280 m)
Lux @ 66' (25 m):	525 Lux
Coverage at 66' (25 m):	132 sq ft (12 sq m)
Rotation:	370° (built in limit stops)
Tilt:	120° Tilt (75° up & 45° down)
Wireless range:	200 ft (65 m)
Dimensions:	7.5"W x 7.5"H x 9.25"D (19cm x 19cm x 23.5cm)
Weight:	3.30 lbs (1.5 kg)
Housing material:	UV resistant PC/ASA
Lens material:	UV resistant Lexan®
Operating temp range:	5°F–113°F (-15°C–45°C)
IP Rating:	IP56

Description	Color	Item #	OEM #
12/24 Volt, 100 Watt	white	<b>SPL-12W</b>	—
12/24 Volt, 100 Watt	black	<b>SPL-12B</b>	—
12/24 Volt, 100 Watt	chrome	<b>SPL-12C</b>	—
12 Volt, 100 Watt	white	—	SPL-12W.OEM
12 Volt, 100 Watt	black	—	SPL-12B.OEM
12 Volt, 100 Watt	chrome	—	SPL-12C.OEM
24 Volt, 100 Watt	white	—	SPL-24W.OEM
24 Volt, 100 Watt	black	—	SPL-24B.OEM
24 Volt, 100 Watt	chrome	—	SPL-24C.OEM

### Replacement Bulbs

Description	Item #
12 Volt, H3 Halogen	<b>202319</b>
24 Volt, H3 Halogen	<b>202320</b>



## Remote Options



### SPLR-2

**Included**

Remote Specifications	Wireless Bridge Remote
Power	12 or 24 volt (hard wired)
Current draw (idle / in use)	negligible
Wireless range	200 ft (65m)
Estimated battery life	—
Dimensions	3.5"Wx2.25"Hx.75"D 88x57x19 mm
Weight	2.12 oz (60g)
Housing material	UV resistant PC/ASA
Button material	Silicone (glow in the dark)
Operating temp range	5°F–113°F (-15°C–45°C)
IP Rating	IP54



### SPLR-1

(optional)

Remote Specifications	Hand Held Bridge Remote
Power	CR2540 button cell battery
Current draw (idle / in use)	negligible
Wireless range	200 ft (65m)
Estimated battery life	> 40 hours (continuous use)
Dimensions	2.0"Wx3.78"Hx1"D 51x96x25 mm
Weight	2.82 oz (80g)
Housing material	UV resistant PC/ASA
Button material	Silicone (glow in the dark)
Operating temp range	5°F–113°F (-15°C–45°C)
IP Rating	IP56



### SPLR-3

(optional)

Remote Specifications	Wired Bridge Remote
Power	12 or 24 volt (hard wired)
Current draw (idle / in use)	negligible
Wireless range	—
Estimated battery life	—
Dimensions	3.5"Wx2.25"Hx.75"D 88x57x19 mm
Weight	2.12 oz (60g)
Housing material	UV resistant PC/ASA
Button material	Silicone (glow in the dark)
Operating temp range	5°F–113°F (-15°C–45°C)
IP Rating	IP54

