



2nm 360° Red, double, silver anodized, with 0,7m cable

200-014G2ST

2nm dbl 360° Red, silver anodized
Horizontal mounted with 0.75m cables

Specifications	
Number	200-014G2ST
Light Color	Red
Dimensions metric	Ø92,5mm x 68mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 2.7"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438016750
IP rating	IP68
Power draw (W)	2,1
UPC Code	879343016784
Connection	0.7m cable
Current consumption (mA @ 12VDC)	150

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	85
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.84 Kg
Weight (Oz)	29.63 Oz