



5nm Masthead, Double, black anodized

300-038-B

5nm dbl masthead (blk), hor CB mnt
 W/aluminium base
 2 outlets at side and 2 outlets at bottom
 Base plate of HD PE for easy install

Specifications	
Number	300-038-B
Light Color	White
Dimensions metric	Ø92,5mm x 128mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Support
Intensity	>52cd
Dimensions imperial	Ø3.6" x 5"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438003361
IP rating	IP68
Power draw (W)	7
UPC Code	879343003364
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications	
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	290
Vessel size	20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	1.65 Kg
Weight (Oz)	58.20 Oz