



## 3nm 112,5° starboard, silver anodized, vertical mount, with 2,5m cable

301-101

3nm stbd, silver anodized  
Vertical mounted with 2.5m cable

Specifications	
Number	301-101
Light Color	Green
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>15cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438013148
IP rating	IP68
Power draw (W)	2,3
UPC Code	879343013141
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	180
<b>Stock status</b>	Usually in stock
<b>Current consumption (mA @ 24VDC)</b>	100
<b>Vessel size</b>	Over 50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.38 Kg
<b>Weight (Oz)</b>	13.40 Oz