



5nm 225° Masthead, silver anodized, vertical mount, with 0,7m cable

301-011

5nm masthead, silver anodized
Vertical mounted with 0,75m cable

Specifications	
Number	301-011
Light Color	White
Dimensions metric	74,55 x 28 x 73,16
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>52cd
Dimensions imperial	2.9" x 1.1" x 2.88"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	5nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009486
IP rating	IP68
Power draw (W)	4,1
UPC Code	879343009489
Connection	0.7m cable

Specifications

Current consumption (mA @ 12VDC)	320
---	-----

Stock status	Usually in stock
---------------------	------------------

Current consumption (mA @ 24VDC)	170
---	-----

Vessel size	20-50M
--------------------	--------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	0.42 Kg
--------------------	---------

Weight (Oz)	14.81 Oz
--------------------	----------