



2nm 112,5° starboard sidelight, single, horizontal mount, black anodised, 2,5m cable

301-008-B

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

- For Boats and Yachts up to 50m (164 ft)
- High quality materials used for long life.
- Water and vibration proof.
- No EMC noise on your AIS/VHF.
- Multivoltage - 12 to 24 Volt.
- Worldwide approvals.
- Including potted-in power cable for ultimate waterproofness.
- 5 year warranty.

Horizontal mounted with 2,5m cable

Specifications	
Number	301-008-B
Light Color	Green
Dimensions metric	Ø92,5mm x 46mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>5.4cd
Dimensions imperial	Ø3.6" x 1.8"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010222
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343010225
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	110
Stock status	Usually in stock
Lead time	1-2 weeks
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.64 Kg
Weight (Oz)	22.57 Oz