



3nm 112,5° port, silver anodized, vertical mount, with 2,5m cable

301-102

3nm port, silver anodized
Vertical mounted with 2.5m cable

Specifications	
Number	301-102
Light Color	Red
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, 2 Mounting screws (M6 * 8 mm), Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438010567
IP rating	IP68
Power draw (W)	2
UPC Code	879343010560
Connection	2.5m cable

Specifications	
Current consumption (mA @ 12VDC)	150
Stock status	Usually in stock
Current consumption (mA @ 24VDC)	100
Vessel size	Over 50M
Min. feed wire gauge	0.5mm ² AWG22
Weight (Kg)	0.39 Kg
Weight (Oz)	13.76 Oz