



## 1nm stbd, silver anodized

101-001

1nm stbd, silver anodized

- New generation
- LED (Light Emitting Diode) navigation light.
- Unique and precise definition of light angles.
- Rugged and unbreakable: Precision machined anodised aluminium housing protects the LED's and electronics.
- Completely waterproof and vibrationproof: Interior is fully filled and sealed with special potting resin.
- Waterproof to IP 68+ (submersible).
- Low power consumption – 70 to 90% less than traditional navigation lights.
- Full brightness with input voltages ranging from 10 to 32 Volts.
- All Lopolights have been tested several times during production, a total of more than 24 hours.
- Easy to install, adaptor and screws included (when applicable).
- See 301-008 for horizontal mounted side light

Specifications	
Number	101-001
Light Color	Green
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>1.2cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	1nm
Included In Package	1 Navigation light, precabled with 2.5 meter shielded marine grade cable, Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438008359
IP rating	IP68
Power draw (W)	1,1
UPC Code	879343008352
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	66
<b>Stock status</b>	Usually in stock
<b>Lead time</b>	1-2 weeks
<b>Current consumption (mA @ 24VDC)</b>	34
<b>Vessel size</b>	Under 12M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.39 Kg
<b>Weight (Oz)</b>	13.76 Oz