



## 2nm Starboard, black anodized

301-001-B

This LED Navigation light comes in black and silver, with the best technology available and impressive robustness. It is easy to install. Below is a list of more great features. For more detailed information, please download technical files.

<>

Vertically mounted with 2,5m cable

Specifications	
Number	301-001-B
Light Color	Green
Dimensions metric	92,5 x 28 x 49,7
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under Support
Intensity	>5.4cd
Dimensions imperial	3.6" x 1.1" x 1.95"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light,2 Mounting screws (M6 * 8 mm),Installation guide
Operating temperature	-25°C to 55°C
Mounting	Vertical
Materials	Black anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438009776
IP rating	IP68
Power draw (W)	1,4
UPC Code	879343009779
Connection	2.5m cable

Specifications	
<b>Current consumption (mA @ 12VDC)</b>	110
<b>Stock status</b>	Usually in stock
<b>Lead time</b>	1-2 weeks
<b>Current consumption (mA @ 24VDC)</b>	60
<b>Vessel size</b>	Under 12M,12-20M,20-50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	0.38 Kg
<b>Weight (Oz)</b>	13.40 Oz