

# NN 3050

RUGGED. MARITIME. GYRO-STABILIZED. LOW MAINTENANCE

NN 3000 Series



### Electro-Optical/Infra-Red camera system

The Night Navigator™ 3050 is a rugged, low maintenance, compact electro-optical system designed for military and paramilitary end users. Mast mounted payload, this imaging system offers exceptional performances. It integrates a **MWIR cooled thermal imager** and a **HD day camera / low light** in a **gyro-stabilized** sensor platform. It can be controlled from the bridge of a ship or through IP network in a control room or remote location. This COTS system is built to MIL Std.

### APPLICATIONS

- ISR (Intelligence, Surveillance and Reconnaissance)
- EEZ (Exclusive Economic Zone) protection
- Long-Range Surveillance
- Unmanned Surface Vessels operation
- Autonomous Vessels
- Maritime SAR
- Safety and security at anchor and in the harbour
- Tracking of potential threat or man overboard
- Situational awareness
- Anti-smuggling operations

### BENEFITS

- **Rugged**, marine, **low maintenance** design
- **Detects** a NATO target over 14km, night and day
- **Provides a clear, highly detailed image**, in HD day, even into the digital zoom range
- **Increases object detection** in low level of light with best of class low light sensitivity
- **Tracks** Radar cursor, ARPA Target, AIS and video targets
- **Streams H.264 (HD)** video with PIP or two video streams and **communicates digitally** over IP network (Ethernet)
- **Outputs video in dedicated coax cable to the bridge in SDI**
- **Enables Picture in Picture (PiP)** of two live video signal outputs (zoom synchronized or independent)
- **Single payload** with no junction boxes or interface modules simplifies installations and retro fits, while reducing maintenance
- **Standard mounting and cabling** for all Night Navigator 3000 series enables ease of payload swaps and future upgrades
- **Designed to withstand marine environmental conditions** and proven by over 15 years and hundreds of successful operating installations worldwide

CURRENT Scientific Corporation – Tel: +1 604 461 5555 – sales@currentcorp.com

[www.currentcorp.com](http://www.currentcorp.com)

# NN 3050

## SYSTEM FEATURES

### THERMAL CAMERA

Spectral Range:	3 – 5 $\mu$ m Cooled thermal imager
Sensor type:	MWIR (InSb FPA)
Resolution:	640x512 pixels
Field of View:	28° (wide) to 2° (narrow)
Zoom:	14x continuous optical zoom
Frequency:	30 fps, full frame rate for export
Detection Range <sup>1</sup> :	NATO target over 14km / Human over 5km

### DAY / LOW LIGHT CAMERA

Sensor type:	1/2.8" CMOS
Field of View:	63° to 2.3° FoV in HD mode, 1080p30
Optical zoom:	30x continuous
Digital zoom:	12x continuous
Window coating:	Hydrophobic

### LOW LIGHT HD CAMERA (FUNCTION)

Sensor type:	1/2.8" CMOS
Low light sensitivity:	0.0015 Lux in B&W mode and 0.0008 Lux in Color mode

### RADAR CURSOR, ARPA & AIS TARGET TRACKING

Slew-to-cue allows target detected from the Radar and AIS to be tracked automatically by the EO/IR. Interface between Radar and AIS over NMEA0183 communication standard in RS232 or RS422, through supplied Network Interface Box. Ship GPS data is also fed through NMEA 0183 communication to register and display the ship's position in Latitude, Longitude, Date, Time and Speed over Ground. Radar target info displayed in videos (ARPA Target, Range and Bearing).

### VIDEO TRACKING OPTION

Automatic pursuit of an object of interest or threat selected on the display by the operator, without any continuous input. Both the infrared and day sensors automatically track the target, even with small obstructions in their path.

### CONTROLLER: HARDWARE OR GUI, IP BASED AND REMOTE-CONTROLLED SOLUTIONS (OPTIONS)

- 1. Video GUI** (with optional USB joystick / Rugged Rigid Grip): video and control combined on panel PC / Laptop.
- 2. Control GUI (Graphical User Interface)**, either on **dedicated touchscreen** display (Panel PC) or as pop up window in PC; with optional USB joystick / Rugged Rigid Grip.
- 3. Compact controller** integrating joystick and 2.4" display for orientation & troubleshooting.
- 4. Protocol for interface to Command & Control System**

All controllers offer Built-in Test for remote diagnostic and are configured for optional additional controllers, remote control, and autonomous navigation.

### PAYLOAD SPECIFICATIONS

System type:	3 axis gyro stabilization <sup>2</sup> c./w. enhanced video stabilization
Pan Range:	Continuous 360° AZ rotation
Tilt range:	+/-90° elevation movement, including stow position
Colour:	Matterhorn White - gloss. Custom colour upon request.

### SYSTEM INTERFACE

Video format:	SDI
Video streaming:	H.264 in HD with PiP or 2 video streams accessed via net0 and net1
Data:	Radar cursor / ARPA target / AIS over NMEA 0183 via RS422 or RS232
Control:	Over IP network

### ENVIRONMENTAL

Ingress Protection Mark:	IP67
Compliant to:	MIL-STD 810 & MIL-STD 461
Operational temperature:	-20°C to +55°C

### WEIGHT AND DIMENSIONS

Weight:	<20 kg
Diameter payload <sup>3</sup> :	239.7mm
Height payload <sup>3</sup> :	431.5mm

### POWER REQUIREMENTS

Voltage:	24 to 36 VDC
Max. Consumption:	320W

### OTHER OPTIONS AND ACCESSORIES

Other sensors: Contact us with your specific requirements.


<sup>1</sup> theoretical calculation using Johnson's criteria & not accounting for atmospheric conditions/ <sup>2</sup> resolved by 2 axis positioning / <sup>3</sup> Larger movement space required



## CONTROL SOLUTIONS



### 1. Video GUI



### 2. Control GUI



### 3. Compact Controller



### 4. Protocol for interface to Command & Control System



2-Button Joystick

Rugged Rigid Grip



**CURRENT**

CURRENT Scientific Corporation – 2933 Murray Street, Port Moody, BC, V3H 1X3, CANADA

Tel: +1 604 461 5555 – sales@currentcorp.com – [www.currentcorp.com](http://www.currentcorp.com)