

*\*refer to product manual for proper installation requirements*

# Vertical Series (25-165 kVA)

The Vertical Series V and VII models feature a slim, narrow design and house the same reliable technology found in the Standard Series. The NV models feature ASEA's latest technology which allows for reduced capacity mode should one module become unavailable.

The Vertical Series is the only product line with a convertible cooling system. These converters come Standard with an Air cooled system, but can be ordered with or field modified to be cooled with a heat exchanger to utilize the vessel's chilled water system.



### Convertible Cooling System

Utilize fans for Air cooling or a heat exchanger system



### Slim & Compact Enclosure

Ideal for tight spaces with minimal horizontal space



### Stainless Steel & Aluminum

Powder coated for ultimate durability and protection

#### POWER RANGE

8 12 15 18 20 25 30 36 45 50 55 63 75 90 100 110 125 150 165 kVA

COMMONLY INSTALLED ON

CRUISERS (10 to 16 meters)

YACHTS (17 to 23 meters)

SUPERYACHTS (24 to 45 meters)

MEGAYACHTS (46-65 meters)

GIGAYACHTS (66 to 90 meters)

### MORE FEATURES

- Auto-Restart from shore brownout or blackout
- Conformal coated printed circuit boards
- Front panel display console
- Minimal harmonic distortion
- Reverse polarization prevention
- Galvanic corrosion protection
- Global support network
- Precision regulation

see specifications on following pages

# Vertical Series (25-165 kVA)

MODEL	AC25VII-1	AC25VII-3	AC30VII-1	AC30VII-3	AC36VII-1	AC36VII-3
PART NUMBER	607516	607517	607518	607519	607537	607538
INPUT POWER FORM	Single, Three	Single, Three	Single, Three	Single, Three	Single, Three	Single, Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520	170-520	170-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70	40-70	40-70
POWER FACTOR	>0.99 @ rated load	>0.99 @ rated load	>0.99 @ rated load	>0.99 @ rated load	>0.99 @ rated load	>0.99 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single	Single	Single
OUTPUT POWER RATING	25 kVA	25 kVA	30 kVA	30 kVA	36 kVA	36 kVA
OUTPUT POWER FORM	Single, Split	Three	Single, Split	Three	Single, Split	Three
UPGRADEABILITY	30 or 36 kVA	30 or 36 kVA	36 kVA	36 kVA	N/A	N/A
OUTPUT VOLTAGE	220 or 230, 120/240 V	120/208, 127/220, 220/380, 230/400, or 240/416 V	220 or 230, 120/240 V	120/208, 127/220, 220/380, 230/400, or 240/416 V	220 or 230, 120/240 V	120/208, 127/220, 220/380, 230/400, or 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load
COOLING	Air	Air	Air	Air	Air	Air
MOUNTING	Floor	Floor	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	L	L	L	L	L	L
WEIGHT	261 kg / 575 lbs	261 kg / 575 lbs	268 kg / 591 lbs	268 kg / 591 lbs	284 kg / 626 lbs	284 kg / 626 lbs
HEIGHT	162.0 cm / 63.8 in	162.0 cm / 63.8 in	162.0 cm / 63.8 in	162.0 cm / 63.8 in	162.0 cm / 63.8 in	162.0 cm / 63.8 in
WIDTH	45.7 cm / 18.0 in	45.7 cm / 18.0 in	45.7 cm / 18.0 in	45.7 cm / 18.0 in	45.7 cm / 18.0 in	45.7 cm / 18.0 in
DEPTH	53.3 cm / 21.0 in	53.3 cm / 21.0 in	53.3 cm / 21.0 in	53.3 cm / 21.0 in	53.3 cm / 21.0 in	53.3 cm / 21.0 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC36V-1	AC36VHE-1	AC36V-3	AC36VHE-3	AC36NV-3	AC36NVHE-3
PART NUMBER	604470	604482	604517	604485	631185	631201
INPUT POWER FORM	Single, Three	Single, Three	Single, Three	Single, Three	Three	Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520	170-520	170-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single	Single	Single
OUTPUT POWER RATING	36 kVA	36 kVA	36 kVA	36 kVA	36 kVA	36 kVA
OUTPUT POWER FORM	Single, Split	Single, Split	Three	Three	Three	Three
UPGRADEABILITY	45 or 54 kVA	45 or 54 kVA	45 or 54 kVA	45 or 54 kVA	45 or 50 kVA	45 or 50 kVA
OUTPUT VOLTAGE	220 V, 230 V, 240 V, 120/240 V	220 V, 230 V, 240 V, 120/240 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load	93% @ rated load	93% @ rated load
COOLING	Air	heat exchanger	Air	heat exchanger	Air	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	L	L	I	I	I	I
WEIGHT	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs	325 kg / 717 lbs	357 kg / 787 lbs
HEIGHT	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in	154.0 cm / 60.6 in	155.6 cm / 61.3 in
WIDTH	63.5 cm / 25 in	64.0 cm / 25.2 in	63.5 cm / 25 in	64.0 cm / 25.2 in	40.6 cm / 16.0 in	40.6 cm / 16.0 in
DEPTH	50.8 cm / 20 in	63.5 cm / 25 in	50.8 cm / 20 in	63.5 cm / 25 in	40.6 cm / 16.0 in	40.6 cm / 16.0 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC45V-1	AC45VHE-1	AC45V-3	AC45VHE-3	AC45NV-3	AC45NVHE-3
PART NUMBER	604471	604483	604518	604486	631187	631203
INPUT POWER FORM	Single, Three	Single, Three	Single, Three	Single, Three	Three	Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520	170-520	170-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single	Single	Single
OUTPUT POWER RATING	45 kVA	45 kVA	45 kVA	45 kVA	45 kVA	45 kVA
OUTPUT POWER FORM	Single, Split	Single, Split	Three	Three	Three	Three
UPGRADEABILITY	54 kVA	54 kVA	54 kVA	54 kVA	50 kVA	50 kVA
OUTPUT VOLTAGE	220 V, 230 V, 240 V, 120/240 V	220 V, 230 V, 240 V, 120/240 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load	93% @ rated load	93% @ rated load
COOLING	Air	heat exchanger	Air	heat exchanger	Air	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	I	I	I	I	NV	NV
WEIGHT	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs	325 kg / 717 lbs	357 kg / 787 lbs
HEIGHT	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in	154.0 cm / 60.6 in	155.6 cm / 61.3 in
WIDTH	63.5 cm / 25 in	64.0 cm / 25.2 in	63.5 cm / 25 in	64.0 cm / 25.2 in	40.6 cm / 16.0 in	40.6 cm / 16.0 in
DEPTH	50.8 cm / 20 in	63.5 cm / 25 in	50.8 cm / 20 in	63.5 cm / 25 in	40.6 cm / 16.0 in	40.6 cm / 16.0 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC54V-1	AC54VHE-1	AC54V-3	AC54VHE-3
PART NUMBER	604472	604484	604519	604487
INPUT POWER FORM	Single, Three	Single, Three	Single, Three	Single, Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single
OUTPUT POWER RATING	54 kVA	54 kVA	54 kVA	54 kVA
OUTPUT POWER FORM	Single, Split	Single, Split	Three	Three
UPGRADEABILITY	N/A	N/A	N/A	N/A
OUTPUT VOLTAGE	220 V, 230 V, 240 V, 120/240 V	220 V, 230 V, 240 V, 120/240 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V, and 254/440 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V, and 254/440 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	91% @ rated load	91% @ rated load	91% @ rated load	91% @ rated load
COOLING	Air	heat exchanger	Air	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	I	I	I	I
WEIGHT	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs	381 kg / 840 lbs
HEIGHT	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in	142.6 cm / 56.1 in
WIDTH	63.5 cm / 25 in	64.0 cm / 25.2 in	63.5 cm / 25 in	64.0 cm / 25.2 in
DEPTH	50.8 cm / 20 in	63.5 cm / 25 in	50.8 cm / 20 in	63.5 cm / 25 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC50NV-3	AC50NVHE-3	AC63NV-3	AC63NVHE-3	AC75NV-3	AC75NVHE-3
PART NUMBER	631189	631205	625037	625055	625039	625057
INPUT POWER FORM	Three	Three	Three	Three	Three	Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520	170-520	170-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
SHORE CORD INPUT	Standard	Standard	Standard	Standard	Standard	Standard
OUTPUT POWER RATING	Single	Single	Single	Single	Single	Single
UPGRADEABILITY	50 kVA	50 kVA	63 kVA	63 kVA	75 kVA	75 kVA
OUTPUT POWER FORM	Three	Three	Three	Three	Three	Three
UPGRADEABILITY	N/A	N/A	75 kVA	75 kVA	N/A	N/A
OUTPUT VOLTAGE	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	93% @ rated load	93% @ rated load	93% @ rated load	93% @ rated load	93% @ rated load	93% @ rated load
COOLING	Air	heat exchanger	Air	heat exchanger	Air	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	NV	NV	NV	NV	NV	NV
WEIGHT	325 kg / 717 lbs	357 kg / 787 lbs	510 kg / 1124 lbs	547 kg / 1206 lbs	510 kg / 1124 lbs	547 kg / 1206 lbs
HEIGHT	154.0 cm / 60.6 in	155.6 cm / 61.3 in	166.0 cm / 65.4 in	165.7 cm / 65.2 in	166.0 cm / 65.4 in	165.7 cm / 65.2 in
WIDTH	40.6 cm / 16.0 in	40.6 cm / 16.0 in	63.5 cm / 25.0 in	63.0 cm / 24.8 in	63.5 cm / 25.0 in	63.0 cm / 24.8 in
DEPTH	53.3 cm / 21.0 in	72.7 cm / 28.6 in	63.5 cm / 25.0 in	64.2 cm / 25.3 in	63.5 cm / 25.0 in	64.2 cm / 25.3 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC90V-3	AC90VHE-3	AC100V-3	AC100VHE-3	AC125V-3	AC125VHE-3
PART NUMBER	605962	605896	605963	605960	605964	605956
INPUT POWER FORM	Three	Three	Three	Three	Three	Three
INPUT VOLTAGE	170-520	170-520	170-520	170-520	330-520	330-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single	Single	Single
OUTPUT POWER RATING	90 kVA	90 kVA	100 kVA	100 kVA	125 kVA	125 kVA
OUTPUT POWER FORM	Three	Three	Three	Three	Three	Three
UPGRADEABILITY	100 kVA	100 kVA	N/A	N/A	N/A	N/A
OUTPUT VOLTAGE	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	120/208 V, 127/220 V, 220/380 V, 230/400 V, 240/416 V	220/380 V, 230/400 V, 240/416 V	220/380 V, 230/400 V, 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	93% @ rated load	93% @ rated load	93% @ rated load	93% @ rated load	94% @ rated load	94% @ rated load
COOLING	Air	heat exchanger	Air	heat exchanger	Air	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	R	R	R	R	R	R
WEIGHT	635 kg / 1400 lbs	635 kg / 1400 lbs	635 kg / 1400 lbs	635 kg / 1400 lbs	795kg / 1753 lbs	828 kg / 1825 lbs
HEIGHT	165.0 cm / 65.0 in	165.0 cm / 65.0 in	165.0 cm / 65.0 in	165.0 cm / 65.0 in	165.0 cm / 65.0 in	166.0 cm / 65.4 in
WIDTH	63.5 cm / 25.0 in	63.5 cm / 25.0 in	63.5 cm / 25.0 in	63.5 cm / 25.0 in	63.5 cm / 25.0 in	63.5 cm / 25.0 in
DEPTH	58.4 cm / 23.0 in	71.1 cm / 28.0 in	58.4 cm / 23.0 in	71.1 cm / 28.0 in	58.4 cm / 23.0 in	71.1 cm / 28.0 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com

# Vertical Series (25-165 kVA)

MODEL	AC125NV-3	AC125NVHE-3	AC150NVHE-3	AC165NVHE-3
PART NUMBER	624511	624512	624516	N/A
INPUT POWER FORM	Three	Three	Three	Three
INPUT VOLTAGE	330-520	330-520	330-520	330-520
INPUT FREQUENCY	40-70	40-70	40-70	40-70
POWER FACTOR	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load	>0.98 @ rated load
AUTO RESTART	Standard	Standard	Standard	Standard
SHORE CORD INPUT	Single	Single	Single	Single
OUTPUT POWER RATING	125 kVA	125 kVA	150 kVA	165 kVA
OUTPUT POWER FORM	Three	Three	Three	Three
UPGRADEABILITY	150 kVA	150 kVA	N/A	N/A
OUTPUT VOLTAGE	220/380 V, 230/400 V, 240/416 V	220/380 V, 230/400 V, 240/416 V	220/380 V, 230/400 V, 240/416 V	220/380 V, 230/400 V, 240/416 V
OUTPUT FREQUENCY	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
OUTPUT CURRENT	See table below	See table below	See table below	See table below
CONVERSION EFFICIENCY	94% @ rated load	94% @ rated load	94% @ rated load	94% @ rated load
COOLING	Air	heat exchanger	heat exchanger	heat exchanger
MOUNTING	Floor	Floor	Floor	Floor
SERIES	Vertical	Vertical	Vertical	Vertical
ENCLOSURE STYLE	Standard	Standard	Standard	Standard
LEGACY ENCLOSURE	NV	NV	NV	NV
WEIGHT	829 kg / 1828 lbs	861 kg / 1898 lbs	861 kg / 1898 lbs	N/A
HEIGHT	172.0 cm / 67.7 in	172.0 cm / 67.7 in	172.0 cm / 67.7 in	172.0 cm / 67.7 in
WIDTH	68.6 cm / 27.0 in	72.9 cm / 28.7 in	72.9 cm / 28.7 in	92.2 cm / 36.3 in
DEPTH	63.5 cm / 25.0 in	76.5 cm / 30.1 in	76.5 cm / 30.1 in	90.7 cm / 35.7 in

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com



# Vertical Series (25-165 kVA)

## OUTPUT CURRENT - NV Models

Output Form	AC36NV-3	AC45NV-3	AC50NV-3	AC63NV-3	AC75NV-3	AC125NV-3	AC150NV-3	AC165NV-3
3 Ø, 277/480 V	43 A/Ø	54 A/Ø	35 A/Ø	76 A/Ø	90 A/Ø	150 A/Ø	-	-
3 Ø, 254/440 V	47 A/Ø	59 A/Ø	66 A/Ø	83 A/Ø	98 A/Ø	164 A/Ø	197 A/Ø	217 A/Ø
3 Ø, 240/416 V	50 A/Ø	63 A/Ø	69 A/Ø	88 A/Ø	104 A/Ø	174 A/Ø	208 A/Ø	229 A/Ø
3 Ø, 230/400 V	52 A/Ø	65 A/Ø	72 A/Ø	91 A/Ø	109 A/Ø	181 A/Ø	217 A/Ø	239 A/Ø
3 Ø, 220/380 V	55 A/Ø	68 A/Ø	76 A/Ø	95 A/Ø	114 A/Ø	189 A/Ø	228 A/Ø	250 A/Ø
3 Ø, 127/220 V	94 A/Ø	118 A/Ø	131 A/Ø	165 A/Ø	197 A/Ø	-	-	-
3 Ø, 120/208 V	100 A/Ø	125 A/Ø	139 A/Ø	175 A/Ø	209 A/Ø	-	-	-

## OUTPUT CURRENT - V & VII Models

Output Form	25 kVA	30 kVA	36 kVA	45 kVA	54 kVA	90 kVA	100 kVA
1 Ø, 220 V	114 A/Ø	136 A/Ø	164 A/Ø	205 A/Ø	245 A/Ø	-	-
1 Ø, 230 V	109 A/Ø	130 A/Ø	157 A/Ø	196 A/Ø	235 A/Ø	-	-
1 Ø, 240 V	104 A/Ø	125 A/Ø	150 A/Ø	187 A/Ø	225 A/Ø	-	-
2 Ø, 120/240 V	104 A/Ø	125 A/Ø	150 A/Ø	187 A/Ø	225 A/Ø	-	-
3 Ø, 120/208 V	70 A/Ø	83 A/Ø	100 A/Ø	125 A/Ø	150 A/Ø	250 A/Ø	278 A/Ø
3 Ø, 127/220 V	66 A/Ø	79 A/Ø	94 A/Ø	118 A/Ø	142 A/Ø	237 A/Ø	263 A/Ø
3 Ø, 220/380 V	38 A/Ø	45 A/Ø	55 A/Ø	68 A/Ø	81 A/Ø	136 A/Ø	156 A/Ø
3 Ø, 230/400 V	36 A/Ø	43 A/Ø	52 A/Ø	65 A/Ø	78 A/Ø	131 A/Ø	145 A/Ø
3 Ø, 240/416 V	35 A/Ø	42 A/Ø	50 A/Ø	63 A/Ø	75 A/Ø	125 A/Ø	139 A/Ø
3 Ø, 254/440 V	-	-	-	59 A/Ø	71 A/Ø	118 A/Ø	131 A/Ø

Huntington Beach, CA, USA

sales@aseapower.com

+1 (714) 896-9695

www.aseapower.com



This product can expose you to lead, a chemical which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information, visit [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Power Systems  
**A/SEA**  
A MISSION CRITICAL ELECTRONICS BRAND