



3nm 225° Masthead/135° stern/360° white, ultra-low, black anodized, horizontal mount, with 6m cable

201-021-B-UL 6M

3nm masthead/stern/360° white, black anodized
Horizontally mounted on a 400-036-B Ultra-low base
With 6m cable.

Specifications	
Number	201-021-B-UL 6M
Light Color	White
Dimensions metric	Ø92,5mm x 36mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on www.lopolight.com under Service & Support
Intensity	>15cd
Dimensions imperial	Ø3.6" x 1.4"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Black anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	10-32VDC
EAN	5704438011144
IP rating	IP68
Power draw (W)	3,6
UPC Code	879343011147
Connection	6m cable
Current consumption (mA @ 12VDC)	300

Specifications

Stock status	Made to order
---------------------	---------------

Current consumption (mA @ 24VDC)	148
---	-----

Vessel size	12-20M
--------------------	--------

Min. feed wire gauge	0.5mm ² AWG22
-----------------------------	--------------------------

Weight (Kg)	0.88 Kg
--------------------	---------

Weight (Oz)	31.04 Oz
--------------------	----------